

Reader/writer Demo Application Instruction



Version 1.4.5

2019.9.25


目录

1.Initialization	3
2.Magcard	7
3.CPU card	9
4.Memory card	11
5.M1FRID card	14
6.UI card.....	18

Comment:The software demo applies to all types of desktop reader and writer devices

with USB interface. However, not all devices support all the listing functions. With any question, or any need for the latest version material, please contact us.

Software Diagram



1. Initialization

Any card operation must be done after successful initialization.

Open the software, if it shows “succeed” at top right corner means it init succeed, but if shows “failed” means there were some problem with the connection. Then, you need to check the connection.

How to confirm whether the device is connected to a computer?

USB insertion to PC and lit on light doesn't mean the device is connected to a computer. Interface aging and wearing will result in dis-communication. Then how to confirm if the device is correctly connected to PC ?

USB connection:

Right click "My Computer" icon ("Computer" for WIN7) —> "management" —> "Human Interface Device" to check if the device is inserted. In addition, unplug the device then insert again, to check if there is any response in "Human Interface Device" to confirm. As picture 1.

Picture 1:



If the device connects but shows a yellow trigon like the picture shows ,it means your computer have find the divce but can`t idedify it. please right click it to update driver

Serial Interface Connection:

Right click "My Computer" ("Computer" for WIN7) —> " Management " —> " Device Manager " —> " port (COM & LPT) " to check the connection.

Baud Rae:

Bard rate refers to Microcontroller or computer transmission rate in serial data communication. We provide two types: 115200 (Baud) and 9600 (Baud) .

Note : When using a serial interface, if it fails to connect, please unplug the device, close software and try again from the begining.

Serial or USB selection should be based on device communication type, as follow picture:
Connection here do not need to switch baud rate or select serial interface number. When select serial and USB interface, click to connect the device, it will show connect successfully. If it fails to show, pull out of device, close software and try again.

That is, only ZCS80, its magnetic card operation part needs to connect to device, the rest operations are the same as those of initialization before.

2.Magnetic Card

Brief introduction: Magcard (magnetic card) applies to many fields. Three tracks are provided to record data with terminal devices,such as credit cards,security cards,membership cards,inquiry cards, stored-valued cards and entrance tickets and so on, which are magnetic recorder dielectric cards. This card is made by high-strength, high-temperature plastic or plastic coated paper so that it's moisture proof wear-resisting and flexible, very easy to carry,and more stable and reliable for use.

magcard demo :

1.click “magnetic card test”,then charge it. Correspondent tip will show when charge successfully(The device supporting encryption can switch to data display format, old type doesn't support.)

2. Click “Stop” to stop the continuous testing function of magnetic card.

Magnetic card function demo:

Demo Software operation procedure:

A. click “IC card reset”, please note: contact IC card and the PSAM deck use 0-4 slot corresponding channel number, while test contactless CPU card, the channel number should be above 5. Proceed subsequent operation after normal reset.

The screenshot shows the software interface with the following elements:

- Navigation tabs: Magnetic Stripe, **CPU Card**, Connect Ic card, M1 Card, 3DES, Ultralight Card
- Information box: IC Reset Success: 6B 00 00 20 90 00 00 00 00 26 D6 8B 94 (circled in red)
- CMD settings:
 - Slot: 0 (Note: 0~4 used for contact, >5 used for contactless, B card any.)
 - APDU fields: CLA (00), INS (84), P1 (00), P2 (00), LC (), Data (), Le (08)
 - Buttons: **IC reset/B Card** (highlighted with a red arrow), IC_off, APDU CMD Send

B. Input APDU commands in the corresponding area when testing, then click “APDU command send” button. The demo software sends APDU commands randomly by default, namely: CLA=0x00, IINS=0x84, P1=0x00, P2=0x00 when data is empty, Le=08.

The screenshot shows the software interface with the following elements:

- Information box: IC APDU Response
C8448A16BE8C9F61
sw1:90
sw2:0 (circled in red)
- CMD settings:
 - Slot: 0 (Note: 0~4 used for contact, >5 used for contactless, B card any.)
 - APDU fields: CLA (00), INS (84), P1 (00), P2 (00), LC (), Data (), Le (08)
 - Buttons: IC reset/B Card, IC_off, **APDU CMD Send** (highlighted with a red arrow)

C. In the “message box” section, you can see the result of returning APDU commands. The corresponding result will be analyzed by SW1, SW2 status bit. SW1:90 SW:00 denotes command operation is successful.

4.Memory Card:

Memory card belongs to logical encryption card,SLE4442 and SLE4448 are common used. security features:


Before password checked correctly, all data only can be read, but not written.

After password checking, only when it's correct, all data can be changed, including the password.

Each byte of protected writing area(first 32 bytes)can be protected read and written individually. After the protected area is written, the content can not be changed.(ie.curing data)

Program Demo:


Write-protected area (first 32 bytes) of each byte can be individually write protected post write-protected content can not be changed (ie, curing data).Currently, the test is mainly to the IC card function of type SLE4442/SLE4428. Take SLE4442 as an example(similar to 4428).




A.

Click “IC card initialization”, after success tip, continue to subsequent operations.


B. Click “4442 check” to test if the IC card is a SLE4442 card. If the tip is “Detected Success!”, the card is a 4442. If test fails, it isn't a 4442 card. After successful test, continue the subsequent operations.




C. Enter card password in the password test area, then click “check password”. Before all the writing operations, the password should be checked first(the password must be correct). The default password has been input by the demo software,please click to check the password directly. D. Click “Read Password”, the card password will show in the message box. E. Change password. Enter new password in the corresponding area as following picture. Enter new password here:112233.




Note: The password has been changed to 112233,if start initialization now, you should enter112233 in the password area to the the password,otherwise, the it will show password incorrect and the subsequent operations can't be proceeded anymore. **Each time operation error appears, please restart initialization and proceed other operations.**



F. Reading cards. Enter the data length in need in the corresponding area as following picture shows. Then click “read”.



G. Writing cards. Input required data in the corresponding area(Hexadecimal data, enter 1234 means 0 x12, 0 x34). Then click “write”



5.M1 Proximity Card

1. For its low price, M1 card is very suitable for use as consumables.
2. Anti-collision, can be used in various applications.
3. Good encryption performance.
4. M1 card door lock system configuration has been updated--- a fully functional communication controller.
5. M1 card door lock system configuration has been updated--- fully open self-service multifunctional software.

select sectors and blocks need to be tested, enter the sector password, click "find the card.

Authorization." If the password is incorrect authorization fails, you can not continue down operations

Demo

A. Select sectors and blocks those needs testing, enter password of that section, click "Request.authorization". If the password is incorrect, authorization will fails, the subsequent operations cannot be continued. After successful authorization, continue the proceeded operations. Please note: All the read and write operations need inputting section password. Please remember.

The screenshot shows the software interface for the M1 Proximity Card. The 'information' section displays a message: "Authorize success..... Type A M1 card SN: 1C-6A-13-D". The 'operate' section contains several controls: 'passtype' with radio buttons for 'KeyA' (selected) and 'KeyB'; 'sector' and 'block' dropdown menus both set to 'Secor00' and 'Block00' respectively; an 'input' section with three rows for '00块', '01块', and '02块', each with a text field containing hexadecimal data and an 'old' field. The '00块' row has 'old' field 'FFFFFFFFFFFF'. The '01块' row has 'new' field empty. The '02块' row has 'update pass' button. At the bottom, there are six buttons: 'Request, authorization' (highlighted with a red circle and arrow), 'Read Block Data', 'Write Block Data', 'Read Sector Data', 'Write Sector Data', and 'Power off'.

B. Click "read block data ", data shows in the the corresponding section area. **The 0 sector 0 block cures M1 card ID information, and all the three sector blocks-3 are configuration password information.** In the following picture, 0 sector 0 block data is being read. And the default setting password has been filled in by the software.

information

Sector0 Block0:1C 6A 13 0D 68 08 04 00 62 63 64 65 66 67 68 69

data from 0-sector 0-block

operate

passtype KeyA KeyB

sector

block

input

00块 11223344556677889900AABBCCDDEEFF old FFFFFFFFFF

01块 11111111111111111111111111111111 new

02块 22222222222222222222222222222222 update pass

Request, authorization Read Block Data Write Block Data Read Sector Data Write Sector Data Power off

C. When writing block data, select the required sector and block, then input required data in the corresponding area on the right. Click “data block write”, after successful writing, the written data can be read directly, as shown in the following figure:

information

write success..

operate

passtype KeyA KeyB

sector

block

input

00块 11223344556677889900AABBCCDDEEFF old FFFFFFFFFF

01块 11111111111111111111111111111111 new

02块 22222222222222222222222222222222 update pass

Request, authorization Read Block Data Write Block Data Read Sector Data Write Sector Data Power off

After successful writing, with confirmation, then to read the second sector o block data:

information

Sector2 Block0:11 22 33 44 55 66 77 88 99 00 AA BB CC DD EE FF

same data

operate

passtype KeyA KeyB

sector

block

input

00块 11223344556677889900AABBCCDDEEFF old FFFFFFFFFF

01块 11111111111111111111111111111111 new

02块 22222222222222222222222222222222 update pass

Request, authorization Read Block Data Write Block Data Read Sector Data Write Sector Data Power off

D. All the data in sector is supported to read(except 03 sector). Select the needed sector, enter the password of the needed sector, with authorization, click “read sector data ” directly.

information

```
Sector2:  
Block 00:11 22 33 44 55 66 77 88 99 00 AA BB CC DD EE FF  
Block 01:11 11 11 11 11 11 11 11 CC CC CC CC CC CC CC CC  
Block 03:22 22 22 22 22 22 22 22 22 22 22 22 22 22 22 22
```

operate

passtype KeyA KeyB

sector **Secor02**

block Block00

input

00块	11223344556677889900AABBCCDDEEFF	old	FFFFFFFFFFFF
01块	11111111111111111111111111111111	new	
02块	22222222222222222222222222222222	<input type="button" value="update pass"/>	

E.Support writing the data of the entire sector once, just click “write sector data ”. All the data can be read after the successful writing. The process of reading the 6th sector data is as following figure.

information

```
Sector6:  
Block 00:11 22 33 44 55 66 77 88 99 00 AA BB CC DD EE FF  
Block 01:11 11 11 11 11 11 11 11 11 11 11 11 11 11 11 11  
Block 03:22 22 22 22 22 22 22 22 22 22 22 22 22 22 22 22
```

operate

passtype KeyA KeyB


sector **Secor06**

block Block00


input

00块	11223344556677889900AABBCCDDEEFF	old	FFFFFFFFFFFF
01块	11111111111111111111111111111111	new	
02块	22222222222222222222222222222222	<input type="button" value="update pass"/>	


write all the data into the 6th sector once.



Then read the data of the 6th sector:as it's shown , the data has been written into the 6th sector.



change password select a sector, enter the current password and new password, then to click “modify area code” As shown in the following picture:change the password of the 13th sector into1111111111, then when new password is needed when visit the 13th sector instead of the default password FFFFFFFFFF.




6.Ultralight Card

Cards or labels, made by NXP MF0 IC U10, conform to ISO14443A. Blank cards, printing cards, paper stickers, key chains, TOKEN, and various sizes and thickness are provided. Mainly applied to: access control, attendance management, meeting attendance, identification, logistics, industrial automation, various membership cards such as canteen, subway, bus tokens, clubs and other consumer electronics, electronic tickets, animal recognition, target tracking, laundry management, one-card-through etc.

Demo Software:

Card searching and selecting operation, as following picture.



Select the block to read data.

Info

```
No3block:11 22 33 44
```

operate

Card Block

Block03

Detect_Select Write Read

Write block data,as shown in the picture:

Info

```
Success Write...
```

operate

Card Block

Block03

Detect_Select Write Read

Let's check the data which is written just now, as shown in the picture:

Info

No3block:11 22 33 44



operate

Card Block

Block03

11223344

Detect_Select

Write

Read

